

Cost-effective transaction management and signature capture system

Symbol's PD4750 is a high performance, highly secure, signature capture payment device that provides fully integrated debit, credit, smart card and contactless payment capabilities. The 16-shade grayscale, pressure resistant touchscreen display enables not only high quality signature capture, but also crisp, on-screen graphics for advertising, and the durable, splash-resistant fixed keypad includes an integrated privacy shield to protect customers from prying eyes during PIN entry. PCI-PED-certified and California ADA-compliant, the PD4750 delivers payment flexibility and fast checkout to your customers while enhancing your revenue generation and cost reduction efforts.

Fast, secure payment processing

Engineered to speed your customers through the checkout, the PD4750's bi-directional, dual-head, 3-track magnetic stripe reader (MSR) and dedicated MSR processor ensure fast, accurate transaction processing, regardless of which way the card is swiped. The combination of advanced communications options, including RS-232, Powered USB, and Ethernet, and Intel XScale 32-bit processor enable rapid data transmission. To ensure the utmost data security, the PD4750 employs an advanced standards-based POS Public Key Encryption, which uses the RSA algorithm to protect against unauthorized applications and PIN compromise attacks. And the durable, splash-resistant fixed keypad includes an integrated privacy shield to further protect consumer privacy during PIN entry.

Easy integration

Integration, as well as updates to transaction flow and screen content, can be achieved faster and at less expense with the PD4750, thanks to the flexible Forms Processing Engine (FPE). FPE is supported by FormBuilder, an intuitive development tool that lets you create standard and custom user screens. OPOS, JavaPOS and direct command interfaces, as well as flexible communications options, further facilitate integration.

Lower TCO, increased revenue

In addition to lower development costs, the PD4750 lowers your TCO through its stable resistive technology, which enables customers to operate the pressure sensitive touchscreen with their fingers or the electronics-free stylus. So, the PD4750 lets you keep serving customers even if the stylus is lost or missing. Electronic signature capture with the PD4750 also significantly reduces the operating and administrative costs associated with paper-based systems, and, since you can retrieve virtually all transaction information instantly, you can also reduce chargeback expenses.



FEATURES

Bi-directional, dual-head, 3-track magnetic stripe reader (MSR); dedicated MSR processor

Advanced hardware and software architecture; high-performance 32-bit processor

16-shade grayscale display

Splash-resistant physical keypad with integrated privacy shield

Resistive pressure-sensitive touchscreen technology

Exclusive auto-sensing screen protection system

Forms Processing Engine and FormBuilder development tool

Variety of communications and connectivity options

Full complement of Windows-based simulator and GUI development tools

BENEFITS

Provides fast, accurate processing, regardless of which way the card is swiped

Delivers the speed and performance required for rapid data transmission

Displays crisp images and ensures high quality signature capture

Maximizes uptime while providing enhanced customer privacy during PIN entry

Enables operation by finger and/or stylus, increasing uptime and reducing TCO

Provides long-lasting display clarity and expands the life of the touchscreen while offering reliable touchscreen performance

Facilitates integration and the creation of custom screens

Ensures compatibility with all host systems

Enables fast and easy integration and rapid prototyping

For more information about how Symbol's PD4750 improves the customer checkout experience, while reducing transaction and payment-related costs, contact us at +1.800.722.6234 or +1.631.738.2400, or visit us on the Web at www.symbol.com/pd4750.

PD4750 Specification Highlights

Physical Characteristics

Dimensions:	8.22 in. L x 6.06 in. W x 2.36 in. H/ 20.9 cm L x 15.4 cm W x 6.0 cm H
Weight:	1.29 lbs/0.59 kg
Display:	16-shade grayscale backlit LCD; 220 x 80 pixels
Touchscreen:	Resistive, transparent, pressure sensitive technology; touchscreen with screen protector; screen protector absence sensor prohibits use without screen protector in place
Keypad:	13 color-coded keys; splash-resistant; hard keycaps; attached privacy shield
Power Source:	AC: 100-240 V, 50/60 Hz DC: 12V @ 700mA or 24 V @ 350mA
Communications:	Mini-DIN port: RS-232 asynchronous; Client USB IBM-retail with power-in (12/24v); 10/100Base-T Ethernet RJ-45 connector
Buzzer:	4.0 KHz (peak) 70 dB minimum level at 1 ft.

Performance Characteristics

Processor:	Intel XScale 200MHz, 32-bit processor
Memory:	4MB Flash/8MB SDRAM (standard)
Card Reader:	Magnetic stripe: Bi-directional, dual-head, 3 track reader (standard) Smart card (optional): EMV level-1; ISO 7816; non-captive; 3v and 5v cards; two 5v SAMs Contactless payment: Integrated (optional); compliant with ISO 14443 A & B; supports American Express, MasterCard and Visa
Encryption:	DES: Visa PED approved; PIN-ANSI X9.8, MAC-ANSI X9.9 Part 1-ANSI X9.24 Triple DES: ANSI X9.52 Key management: DUKPT and master/session keys
Reliability:	100,000 hours (MTBF calculated)
Screen Development:	FormBuilder application development tool

Peripherals and Accessories

SDK Suite:	FPE Developers Toolkit <ul style="list-style-type: none"> Win32: Windows 2000/XP DOS IBM 4690/IBM EFT Protocol OPOS JPOS
------------	---

Regulatory

Electrical Safety:	CE, UL
EMI/RFI:	FCC Class B, CISPR B

Environment

Temperature:	0 - 45° C/32-115° F
Humidity:	Maximum 85%, non-condensing
ESD:	12,000 volts

About Symbol Technologies

Symbol Technologies, Inc., The Enterprise Mobility Company™, is a recognized worldwide leader in enterprise mobility, delivering products and solutions that capture, move and manage information in real time to and from the point of business activity. Symbol enterprise mobility solutions integrate advanced data capture products, radio frequency identification technology, mobile computing platforms, wireless infrastructure, mobility software and world-class services programs. Symbol enterprise mobility products and solutions are proven to increase workforce productivity, reduce operating costs, drive operational efficiencies and realize competitive advantages for the world's leading companies. More information is available at www.symbol.com



Corporate Headquarters
Symbol Technologies, Inc.
 One Symbol Plaza
 Holtsville, NY 11742-1300
 TEL: +1.800.722.6234
 +1.631.738.2400
 FAX: +1.631.738.5990

For Asia Pacific Area
Symbol Technologies Asia, Inc.
 (Singapore Branch)
 Asia Pacific Division
 230 Victoria Street #12-06/10
 Bugis Junction Office Tower
 Singapore 188024
 TEL: +65.6796.9600
 FAX: +65.6796.7199

For Europe, Middle East and Africa
Symbol Technologies
 EMEA Division
 Symbol Place, Winnersh Triangle
 Berkshire, England RG41 5TP
 TEL: +44.118.9457000
 FAX: +44.118.9457500

For North America, Latin America and Canada
Symbol Technologies
 The Americas
 One Symbol Plaza
 Holtsville, NY 11742-1300
 TEL: +1.800.722.6234
 +1.631.738.2400
 FAX: +1.631.738.5990

Symbol Web Site
 For a complete list of Symbol subsidiaries and business partners worldwide contact us at:
www.symbol.com
E-mail
info@symbol.com



Part No. DS-PD4750 Printed in USA 07/06 © Copyright 2006 Symbol Technologies, Inc. All rights reserved. Symbol is an ISO 9001 and ISO 9002 UKAS, RVC, and RAB Registered company, as scope definitions apply. Specifications are subject to change without notice. Symbol® is a registered trademark of Symbol Technologies, Inc. All other trademarks and service marks are proprietary to their respective owners. For system, product or services availability and specific information within your country, please contact your local Symbol Technologies office or Business Partner.