

**Honeywell Sensing and Productivity Solutions**

Tamaulipas 141 1er piso, Hipódromo Condesa  
06140 México, D.F.  
Tel. +52 55 52414800  
www.honeywellaidc.com

**YOUJIE**  
by Honeywell

## ZL2200 Lector tipo pistola Láser



Youjie ZL2200 is a cost-effective single-line laser scanner with optimized performance. As an entry level bar code scanner targeting the low to middle segment of the AIDC markets, ZL2200 is ideal for various scanning applications like retail POS for small supermarkets and convenience stores, document scanning for office automation, and mail and parcels processing for post offices.

### Features

- **Scan performance at an affordable price ratio:** Highly cost effective, ideal for small- to medium-sized enterprises
- **Proprietary scanning platform:** Revolutionary scanning platform design with pending intellectual property rights (IPR)
- **Outstanding scanning performance:** Provides faster scanning, larger depth of field, wider scanning angle and zero error rates.
- **Ergonomic form factor design:** Gun shape design comfortably fit in any hand size, reducing fatigue over long time use
- **High compatibility:** “Plug-and-play” with “no extra setting” enables quick integration with various office devices.

## Honeywell Sensing and Productivity Solutions

Tamaulipas 141 1er piso, Hipódromo Condesa

06140 México, D.F.

Tel. +52 55 52414800

www.honeywellaidc.com

# YOUJIE

by Honeywell

Technical Specifications	ZL2200
Light Source	Visible Laser Diode, 650 nm ± 10 nm
Scan Pattern	single line
Scan Speed	100 scan lines per second
Scan Angle	horizontal 55°
Print Contrast	20% minimum reflection difference
Pitch, Skew	68°, 52°
Light Levels	0 - 100,000LUX
Decode Capabilities	All standard 1D bar codes

Typical Performance *	
Narrow Width	Depth of Field
UPC-A 13 mil	17mm - 232 mm
7.5mil	20mm -163mm
5mil	47mm -111mm
Resolution: 4.5 mil	
*Performance may vary depending on the bar code quality and scanning environment	

Technical Specifications	ZL2200
Input voltage	4.75 ~ 5.25 VDC
Operating power	1.0W (200mA @ 5V)
Standby power	0.7W (140mA @ 5V)
EMI	Class B
Operating Temp.	0 ~ 40 °C
Storage Temp.	-40 ~ 60 °C
Humidity	0% ~ 95% relative humidity, non-condensing