

Honeywell Sensing and Productivity Solutions

Tamaulipas 141 1er piso, Hipódromo Condesa
06140 México, D.F.
Tel. +52 55 52414800
www.honeywellaidc.com

YOUJIE
by Honeywell

HH360 Lector tipo pistola Linear Imager



HH360 provides hassle free scanning performance in scan-intensive or light industrial applications as well. Being highly durable and wearable, HH360 linear-imaging scanner is one of the toughest general duty scanners on the market, designed to keep any operation running smoothly.

Features

- **Superior Hand-held Scanning Performance:** Increases throughput with intuitive hand-held scanning performance
- **Comfort, Ergonomic Design:** Ensures operator comfort and productivity with a gun-shaped form factor optimized for intensive hand-held scanning
- **Class-Leading Reliability:** Increases up time and reduces additional service costs with a reliable design that utilizes no moving parts and full impact resistant bumpers
- **The Latest 1D Imaging Scan Engine:** Enables long distance and high speed scanning with a superior linear decoding software

Honeywell Sensing and Productivity Solutions

Tamaulipas 141 1er piso, Hipódromo Condesa

06140 México, D.F.

Tel. +52 55 52414800

www.honeywellaidc.com

YOUJIE

by Honeywell

Technical Specifications

Mechanical/ Electrical

Dimensions (L x W x H): 98mm×126mm×155mm

Weight: 140g

Input Voltage: 5 ± 0.5VDC

Operating Power: 900mW, 180mA(Typical) @5VDC Standby

Power: 500mW, 100mA(Typical)@5VDC

Interface: USB, RS232, KBW

Scanning Performance

Scan Pattern: Single line

Scan Speed: 300 scans/s

Print Contrast: 20%

Pitch, Skew: 65°, 75°

Minimum Width: 3 mil

Decode Capabilities: Reads all standard 1D and GS1 DataBarT

MSymbologies

Environmental

Operating Temperature: 0°C to 50°C

Storage Temperature: -40°C to 60°C

Humidity: 95%

Drop: 1- 1.5m at random

Environmental Sealing: IP40

Light Levels: 0 to 70, 000LUX

Typical Performance	
Narrow Width	Depth of Field
4mil Code39	85mm – 155mm
5mil Code39	75mm – 200mm
7.5mil Code39	55mm – 315mm
10mil Code39	25mm – 415mm
13mil UPC-A	20mm – 500mm
20mil Code39	20mm – 650mm